SAFETY DATA SHEET FREE AEROSOL

Supercedes Date: 08/22/2023

Issuing Date: 04/25/2024

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: FREE AEROSOL Recommended use Lubricant Information on Manufacturer CERTIFIED LABS, DIV. OF NCH CORP.

BOX 152170 IRVING, TEXAS 75015 Product Code: 12061187 Chemical nature Solvent blend **Emergency Telephone** CHEMTREC® 800-424-9300 Telephone inquiry 972-579-2477

2. HAZARD IDENTIFICATION

Color Amber

Physical state Liquid

Odor Solvent

Appearance Transparent - Hazy

GHS

Classification Physical Hazards

Flammable aerosols Gases under pressure

Health Hazard

Serious eye damage/eye irritation Specific target organ toxicity (single exposure)

Aspiration hazard

Category 1 Compressed gas

Category 2A Category 3 Category 1

Hazards not otherwise classified (HNOC)

Not applicable

Labeling Signal word Danger



Hazard statements

Extremely flammable aerosol May cause drowsiness or dizziness Causes serious eye irritation May be fatal if swallowed and enters airways Contains gas under pressure; may explode if heated

Precautionary statements

Keep away from heat, sparks, open flames or hot surfaces. Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use Do not breathe vapor, gas or mist.

Use in a well-ventilated area.

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves, protective clothing and eye protection.

Do not eat, drink or smoke when using this product

If eye irritation persists: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a physician if unwell.

IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.

Store in a well-ventilated place. Keep container tightly closed

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Dispose of contents and container in accordance with applicable regulations

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
Petroleum distillates, hydrotreated light (<3% DMSO; VF VP: 0.02)	64742-47-8	15-40
Ethyl acetate	141-78-6	10-30
Isobutane	75-28-5	3-7
Propane	74-98-6	3-7

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do

J

not rub affected area. Get medical attention if irritation develops and persists.

Skin contact No hazards which require special first aid measures.

Inhalation Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has

stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth -to-mouth resuscitation. If breathing is difficult, (trained personnel should)

give oxygen. Get immediate medical attention. Delayed pulmonary edema may occur.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious

person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate

medical attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) invol ved,

involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid direct contact with skin. Use barrier to give mouth to-mouth resuscitation. Use personal protective equipment as required. Avoid contact with skin,

eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms Difficulty in breathing. Coughing and/or wheezing. Dizziness. May cause redness and tearing of the

eyes. Burning sensation.

Indication of any immediate medical attention and special treatment needed

Note to physicians

Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the

risk is justified by the presence of additional toxic substances.

5. FIRE-FIGHTING MEASURES

Flash Point > 81 °F / > 27 °C

Method Seta closed cup

Flammability Limits in Air %: Solvent mixture.

Upper flammability limit: 11.5

Lower flammability limit: 1.9

Suitable Extinguishing Media
Water spray. Carbon dioxide (CO2). Foam. Dry chemical. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific hazards arising from the chemical

Solvent vapors are heavier than air and may spread along floors. Vapors may ignite and explode. Flame extension: >24 inches / >61 cm and Burnback: 3 inch / 7.5 cm. Material can create slippery conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure -demand, NOHSC (approved or equivalent) and full protective gear.

Aerosol Level (NFPA 30B) -

3

Flammability 4

Stability 0

NFPA HMIS

Health hazards 2 Health hazards 2

Flammability 4

Physical Hazard 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Use personal protective equipment. Remove all sources of ignition. Ensure adequate

ventilation. Prevent further leakage or spillage if safe to do so. Material can create slippery

conditions.

Environmental precautions Methods for Containment Do not flush into surface water or sanitary sewer system.

Contain spillage, soak up with non -combustible absorbent material, (e.g. sand, earth,

diatomaceous earth, vermiculite) and transfer to a container for disposal according to local /

national regulations (see section 13).

Methods for Cleaning Up

Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly labeled

containers.

Neutralizing Agent

Not applicable.

7. HAN NG AND STORAGE

Handling

Keep away from heat and sources of ignition. Avoid contact with skin, eyes and clothing. Do not

breathe mist, vapor or gas.

Storage

Keep away from open flames, hot surfaces and sources of ignition. Store in original container. Keep

containers tightly closed in a dry, cool and well-ventilated place.

Storage Temperature

35 °F / 2 °C Minimum X

Maximum

ס

120 °F / 49 °C

Storage Conditions

Indoor

Outdoor

Heated

Refrigerated

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical name	CAL/OSHA PEL	ACGIH TLV	OSHA PEL	NIOSH
Petroleum distillates, hydrotreated light (<3% DMSO; VP: 0.02)	No data available	525 mg/m ³ TWA	Not listed	No data available
Ethyl acetate	400 ppm	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m ³	2000 ppm TWA: 400 ppm TWA: 1400 mg/m ³
Isobutane	No data available	STEL: 1000 ppm	No information available	TWA: 800 ppm TWA: 1900 mg/m ³
Propane	1000 ppm	Simple Asphyxiant. Significant quantities of component may displace oxygen, which is the limiting factor for exposure. See Appendix F of ACGIH Threshold Limit Values for Chemical Substances and Physical Agents for more information.	TWA: 1000 ppm TWA: 1800 mg/m ³	2100 ppm STEL 1250 ppm STEL 2250 mg/m ³ TWA: 1000 ppm TWA: 1800 mg/m ³

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this shoul d should be achieved by the use of local exhaust ventilation and good general extraction.

Personal Protective Equipment Eye/Face Protection

Skin Protection

Respiratory Protection

Tightly fitting safety goggles.

Wear suitable protective clothing, Impervious gloves.

In case of insufficient ventilation wear suitable respiratory equipment. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

General Hygiene Considerations

Ensure that eyewash stations and safety showers are close to the workstation location. Remove

and wash contaminated clothing before re -use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state Color

Liquid

Amber Not applicable Kinematic viscosity Odor

No data available Solvent

Odor threshold рΗ **Evaporation Rate**

No information available 19.12 (Butyl acetate=1)

Transparent - Hazy Appearance Specific Gravity 0.797

VOC content Product VP (mmHg @ 70°F) 41.90 1362.3

Percent Volatile (Volume) 75.2 333.9 VOC Content (g/L) Relative vapor density 1.4 No data available

Solubility(ies) Melting Point/Range Initial boiling point and Negligible No data available > 160 °F / 71 °C

n-Octanol/Water Partition Decomposition temperature Flammability (solid, gas)

No data available No data available

boiling range Flash Point

> 81 °F / > 27 °C

Seta closed cup

Autoignition Temperature Flammability Limits in Air %: No information available Solvent mixture

Upper flammability limit: 11.5 Lower flammability limit: 1.9

10. STABILITY AND REACTIVITY

Method

Chemical Stability Conditions to Avoid Incompatible Products

Decomposition temperature Hazardous decomposition products

Possibility of Hazardous Reactions

Stable. Hazardous polymerization does not occur.

Keep away from open flames, hot surfaces, and sources of ignition. Strong oxidizing agents, Reducing agents, Strong acids, Strong

bases, Amines, Nitric acid.

No data available

Carbon oxides, Nitrogen oxides (NOx), Sulfur oxides, Aldehydes, Ketones, Hydrocarbons.

None under normal processing.

11. TOXICOLOGICAL INFORMATION

Product Information

No information available

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) ATEmix (dermal) No information available No information available

Inhalation LC50

No information available

ATEmix (inhalation-gas) ATEmix (inhalation-dust/mist) ATEmix (inhalation-vapor)

No information available No information available

Principle Route of Exposure Primary Routes of Entry

Inhalation, Skin contact, Eye contact. Skin contact, Skin Absorption.

Acute Effects:

Eyes

Causes serious eye irritation.

Skin Inhalation

Ingestion

Chronic toxicity

Low hazard for usual industrial or commercial handling.

May cause irritation of respiratory tract. Inhalation may cause central nervous system effects. May cause central nervous system depression. Symptoms and signs include headache, dizziness,

fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard if

כי

swallowed - can enter lungs and cause damage. May be fatal if swallowed and enters airways. Repeated and prolonged exposure to solvents may cause brain and nervous system damage.

Target organ effects **Aggravated Medical Conditions** Central nervous system, Respiratory system, Skin, Eyes. Respiratory system, Skin disorders, Neurological disorders.

Component Information

Acute Toxicity

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50	Draize Test	Others
Petroleum distillates, hydrotreated light (<3% DMSO; VP: 0.02) 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h	No data available	No data available
Ethyl acetate 141-78-6	= 5620 mg/kg (Rat)	> 18000 mg/kg (Rabbit)	= 4000 ppm (Rat) 4 h	No data available	No data available
Isobutane 75-28-5	No data available	No information available	= 658 mg/L (Rat) 4 h	No data available	No data available
Propane 74-98-6	No data available	No information available	658 mg/L (Rat) 4h	No data available	No data available

Chronic Toxicity

Chemical name	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Petroleum distillates, hydrotreated light (<3% DMSO; VP: 0.02) 64742-47-8	No data available	No data available	No data available	No data available	Eyes Skin
Ethyl acetate 141-78-6	No data available	No data available	No data available	No data available	Skin Eyes Respiratory system
Isobutane 75-28-5	No data available	No data available	No data available	No data available	Central Nervous System
Propane 74-98-6	No data available	No data available	No data available	No data available	Central Nervous System Respiratory system

Carcinogenicity

There are no known carcinogenic substances in this product.

12. ECOLOGICAL INFORMATION

Product Information No information available

Persistence and Degradability

No information available

Bioaccumulation Mobility

No information available No information available

Additional Ecological

No information available

Information:

Component Information

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to microorganisms	Crustacea	Partition coefficie nt
Petroleum distillates, hydrotreated light (<3% DMSO; VP: 0.02)	No information available	LC50 = 2.2 mg/L Lepomis macrochirus 96 h LC50 = 2.4 mg/L Oncorhynchus mykiss 96 h LC50 = 45 mg/L Pimephales promelas 96 h	No information available	No information available	-
Ethyl acetate	No information available	LC50 220 - 250 mg/L Pimephales promelas 96 h LC50 352 - 500 mg/L Oncorhynchus mykiss 96 h LC50 = 484 mg/L Oncorhynchus mykiss 96 h	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h	560: 48 h Daphnia mag magna mg/L EC50 Static	0.6
Isobutane	No information available	No information available	No information available	No information available	2.88
Propane	No information available	No information available	No information available	No information available	2.3

Persistence and degradability

Bioaccumulation

Mobility

No information available.

No information available.

No information available.

13. DISPOSAL CONSIDERATIONS

Product Disposal Container Disposal Dispose of in accordance with local regulations.

Contents under pressure. Do not puncture. Empty remaining contents. Empty containers should be

ヮ

taken for local recycling, recovery, or waste disposal.

14. TRANSPORT INFORMATION

DOT

Proper shipping name

Transport hazard class(es)

AEROSOLS, FLAMMABLE

Description

UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD QTY

UN proper shipping name

Transport hazard class(es)

UN number or ID number

Description

AEROSOLS, FLAMMABLE

2.1 UN1950

UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD QTY

ICAO (air)

UN number or ID number

UN proper shipping name

Transport hazard class(es)

Description

UN1950

AEROSOLS, FLAMMABLE

UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD QTY

IATA

UN number or ID number

UN1950

UN proper shipping name

AEROSOLS, FLAMMABLE

Transport hazard class(es) Description

UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD QTY

IMDG

UN proper shipping name

AEROSOLS

Transport hazard class(es) UN number or ID number

UN1950

Description

UN1950, AEROSOLS, 2.1, LTD QTY

15. REGULATORY INFORMATION

Inventories

TSCA DSL/NDSL Listed

US Federal Regulations

Listed

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals

which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40

7

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs
Ethyl acetate	5000 lb	-

16. OTHER INFORMATION

Prepared By

Adrienne McKee 08/22/2023

Supercedes Date: Issuing Date: Revision Note

04/25/2024 No information available No information available

Glossary List of References.

No information available

CERTIFIED LABS, DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.