

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 001

Date Prepared: 01-14-02

Date Printed: 03/12/04

MSDS No: 0091437-009.011

AUTO PRIDE 80W90 GEAR OIL AU7831

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: AUTO PRIDE 80W90 GEAR OIL AU7831

General or Generic ID: PETROLEUM BASED-LUBRICATING OIL

Company

The Valvoline Company

P.O. Box 14000

Lexington, KY 40512

Telephone Numbers

Emergency: 1-800-274-5263

Information: 1-859-357-7206

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
ALIPHATIC PETROLEUM DISTILLATE		87.0- 97.0
GEAR OIL ADDITIVE		3.6- 14.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Unlikely to cause eye irritation or injury.

Skin

Prolonged or repeated contact may dry and crack the skin.

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation

Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful.

Continued on next page

AUTO PRIDE 80W90 GEAR OIL AU7831

Symptoms of Exposure

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea)

Target Organ Effects

No data

Developmental Information

No data

Cancer Information

This material is not listed as a carcinogen by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration.

Other Health Effects

No data

Primary Route(s) of Entry

Skin contact.

4. FIRST AID MEASURES

Eyes

If eye contact with liquid occurs, hold eyelids apart and flush eyes gently with lukewarm water. Seek immediate medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Swallowing

Do not induce vomiting. Give one glass of milk or water, and get medical attention immediately. If possible, do not leave victim unattended.

Continued on next page

AUTO PRIDE 80W90 GEAR OIL AU7831

Inhalation

First aid is not normally required. If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention.

Note to Physicians

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin.

5. FIRE FIGHTING MEASURES

Flash Point

300.0 F (148.8 C) COC

Explosive Limit

Not applicable

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Fire and Explosion Hazards

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Dense smoke may be generated while burning.

Extinguishing Media

regular foam, water fog, carbon dioxide, dry chemical.

Fire Fighting Instructions

Water or foam may cause frothing which can be violent and possibly endanger the life of the firefighter.

NFPA Rating

Health - 1, Flammability - 1, Reactivity - 0

Continued on next page

AUTO PRIDE 80W90 GEAR OIL AU7831

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

Large Spill

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent, or other absorbent material and shoveled into containers.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Avoid prolonged or repeated contact.

Storage

Keep containers closed when not in use.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Not required under normal conditions of use. However, if misting or splashing conditions exist, then safety glasses or chemical splash goggles are advised.

Skin Protection

Not normally required. However, wear resistant gloves such as nitrile rubber to prevent irritation which may result from prolonged or repeated skin contact with product.

Continued on next page

AUTO PRIDE 80W90 GEAR OIL

AU7831

Respiratory Protections

Not required under normal conditions of use. However, if oil mists are generated above recommended PEL/TLV of 5 mg/m³, then a NIOSH/MSHA approved respirator is advised in absence of proper environmental control. (See your industrial hygienist.)

Engineering Controls

Not required under normal conditions of use. However, if unusual operating conditions exist, then provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below PEL/TLV (s).

Exposure Guidelines

Component

ALIPHATIC PETROLEUM DISTILLATE

No exposure limits established

GEAR OIL ADDITIVE

No exposure limits established

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

(for component) > 425.0 F (218.3 C)

Vapor Pressure

Not applicable

Specific Vapor Density

No data

Specific Gravity

.890 @ 60.00 F

Liquid Density

7.480 lbs/gal @ 60.00 F

.890 kg/l @ 15.60 C

Continued on next page

The Valvoline Company

Page 006

Date Prepared: 01-14-02

Date Printed: 03/12/04

MSDS No: 0091437-009.011

AUTO PRIDE 80W90 GEAR OIL

AU7831

Percent Volatiles (Including Water)

No data

Evaporation Rate

Appearance

State

LIQUID

Physical Form

No data

Color

AMBER

Odor

PETROLEUM

pH

Not applicable

Viscosity

14.0 - 15.0 cst

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Chemical Stability

Stable. Avoid heat, open flame, and prolonged storage at elevated temperatures.

Continued on next page

The Valvoline Company

Page 007

Date Prepared: 01-14-02

Date Printed: 03/12/04

MSDS No: 0091437-009.011

AUTO PRIDE 80W90 GEAR OIL AU7831

Incompatibility

Avoid contact with: strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

Not Regulated

Container/Mode:

CASES/SURFACE - NO EXCEPTIONS

NOS Component:

None

RQ (Reportable Quantity) - 49 CFR 172.101

Not applicable

Continued on next page

The Valvoline Company

Page 008

Date Prepared: 01-14-02

Date Printed: 03/12/04

MSDS No: 0091437-009.011

AUTO PRIDE 80W90 GEAR OIL AU7831

15. REGULATORY INFORMATION

US Federal Regulations

CERCLA RQ - 40 CFR 302.4

None

SARA 302 Components - 40 CFR 355 Appendix A

None

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate() Delayed() Fire() Reactive() Sudden

Release of Pressure()

SARA 313 Components - 40 CFR 372.65

None

International Regulations

Inventory Status

Not determined

State and Local Regulations

California Proposition 65

None

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Last page