Cling Un MATERIAL SAFETY DATA SHEET This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174 IDENTITY AND DISTRIBUTOR'S INFORMATION NFPA Reting: Health-3; Flammability-0; Reactivity-0; Special -HMIS Rating: Health-3; Flammability-0; Reactivity-0; Personal Protection-B Century Labs, Manufactured For: DOT Hazard Classification: Corrosive Material, 8 Address: 3200 S. 24th Street dentity (trade name as used on label): Address: Kansas City, Ks 66106 MSDS Number: A 931 Revision -1 Phone: (913) 262-0227 EMERGENCY RESPONSE NUMBER: 1-800-535-5053 NOTICE: JUDGMENT BASED ON INDIRECT TEST DATA Date Prepared: 15 March 1996 Prepared By: RC/IB Information Calls: (770)422-2071 SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION COMPONENTS-CHEMICAL NAMES AND COMMON NAMES CAS Number OSHA PEL ACGIH Carcinogen III LIST Hazardous Components 1% or greater; Carcinogens 0.1% or greater) TLV (ppm) ppm Raf. Source * 7647-01-0 Yes 5 Hydrogen Chloride 5 d N-Alkyl (C12-C18) -N,N- Dimethyl-N-Benzyl-Ammonlum Chloride 68391-01-5 No N/E N/E d Alkyl Dimethyl Ethyl Benzyl Ammonium Chioride 68956-79-6 No NE NE d SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS Bolling Point: 212°F Specific Gravity (H2O=1): 1.02 Vapor Pressure: PSIG @ 70°F (Aerosols): N/A Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A Evaporation Rate (water= 1): 1 Vapor Density (Air = 1): N/A Solubility in Water: Total Water Resettive: None Appearance and Odor: Opaque blue fluid with mint odor. SECTION 3 - FIRE AND EXPLOSION HAZARD DATA FLAMMABILITY as per USA FLAME PROJECTION TEST Auto Ignition Temperature Flammability Limits in Air by % in Volume: % LEL: N/A % UEL: N/A N/A (aerosols) N/A SPECIAL FIRE FIGHTING PROCEDURES: Wear MIOSK approved breathing FLASH POINT AND METHOD USED (non-aerosols); None apparatus & full protective gear when fighting fires. Spray containers with water to keep cool & prevent ruptures. EXTINGUISHER MEDIA: Non-Combustible. Unusual Fire & Explosion Hazarda: Avoid exposure to matals, oxidants which might product flammable hydrogen gas. SECTION 4 - REACTIVITY HAZARD DATA HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT STABILITY [X] STABLE [] UNSTABLE incompatibility (Mat. to avoid): Bases, metals, mercuric sulfate, carbides of Conditions to Avoid: Contact with strong bases can cause violent reaction generating large amounts of heat. salcium, cestam, rubidium. Hazardous Decomposition Products: Hydrogen gas. SECTION 5 - HEALTH HAZARD DATA PRIMARY ROUTES OF ENTRY: [X]INHALATION [| INGESTION | X | SKIN ABSORPTION | X | EYE |] NOT HAZARDOUS ACUTE EFFECTS Inhalation: Initant causing burning, choking, coughing, headache. Eye Contact; Irritation, severe burns & permanent damage including blindness. Skin Contact: Burning, Irritation, dermatitis,

Ingestion: Unlikely route-causes severe burns to internal organs.

CHRONIC EFFECTS: None known.

Medical Conditions Generally Aggravated by Exposure: Skin, eye, mucous membrane imitation.

EMERGENCY FIRST AID PROCEDURES

Eye Contact: Wash eyes for 15 minutes. Get innnediate medical attention,

Skin Contact: Remove contaminated clothing, wash skin with water for 15 minutes.

Inhalation: Move to tresh air. Get medical attention.

Ingestion: DO NOT INDUCE VOMITING. Drink 3 to 4 glasses of water. Get immediate medical attention.

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

Respiratory Protection (specify type): Approved self-contained breathing apparatus when use concentrations exceed 100 ppm HCl vapors.

Protective Gloves: Neoprene.

Eye Protection: Chemical goggles or face shield.

Vertiliation Requirements: As necessary to maintain air concentration below 5 ppm at all times

Other Protective Clothing & Equipment: Neoprene or PVC rain suit & boots in case of fire. Safety showers & eyewash stations should be available.

Hyglanic Work Practices: Wash hands after use. Do not eat, drink or smoke in Immediate area.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken If Material Is Spilled Or Released: Contain fluid by dising. Neutralize with soda ash or baking soda.

Waste Disposal Methods: Neutralize material may be washed down the sewer. Absorbed material to be boxed and disposed of in compliance with local, state and dederal regulations.

Precautions To Be Taken In Handling & Storage: Store in closed labeled containers. Keep in cool, metal free area for not more than one year.

Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Do not store near strong alkalies or other reactive materials.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

^{**} Chemical Listed as Carcinogen er Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only