

update 2/06
AK

MATERIAL SAFETY DATA SHEET

***** SECTION I *****

MANUFACTURER NAME

EEZ Products Division
Mullen Circle Brand, Inc.
3514 West Touhy Ave
Chicago, Illinois 60645

EMERGENCY PHONE NUMBER

INFOTRAC 800-535-5053

TECHNICAL ASSISTANCE
847-676-1880

Revision Date 1/06

PRODUCT
Foamy Cutting Fluid

CHEMICAL FAMILY Solvent/Oil Blend

***** SECTION II – HAZARDOUS INGREDIENTS *****

INGREDIENT	PERCENT	TLV/PEL/STEL
CAS# 64742-47-8	1.0%+	ACGIH: 100 PPM 8 HR TWA
CAS # 68476-85-7 (Propellant)	1.0%+	ACGIH: 1000PPM PEL

Not Listed As A Carcinogen By NTP, ACGIH, OSHA, IARC

D.O.T. SHIPPING CLASSIFICATION (49CFR172) :Petroleum Distillates UN1268

***** SECTION III – PHYSICAL DATA *****

APPEARANCE AND ODOR : Gold Fluid; Mild Ether Odor
SPECIFIC GRAVITY, 60 F : 0.9
BOILING POINT, F : Not Determined
MELTING POINT, F : Not Applicable
VAPOR DENSITY : Not Determined
SOLUBILITY IN WATER : None
VOLATILES, VOL% : 50% Maximum
EVAPORATION RATE : Slower than Ether

***** SECTION IV – FIRE & EXPLOSION DATA *****

AEROSOL FLAMMABILITY : Considered Flammable As Described in 16 CFR 1500.45
FLASH POINT, F (METHOD) : 159 F (after Propellant Evaporation)
FLAMMABLE LIMITS : (Propellant) Lower 2.2% Upper 9.5%
EXTINGUISHING MEDIA : Foam, CO2, Dry Chemicals, Water Fog Or Mist
FIRE FIGHTING PROCEDURES : Keep Exposed Containers Cool. Fire Fighters Should
Wear Self-Contained Breathing Apparatus.

***** SECTION V – HEALTH HAZARD DATA *****

EFFECTS OF EXPOSURE:

EYES: Liquid and vapor may cause moderate irritation. SKIN: Prolonged or repeated exposure may cause irritation. INHALATION: Prolonged exposure can be irritating to eyes, nose, and respiratory tract. INGESTION: Irritating to the mouth, throat, and stomach. May cause nausea, vomiting, pain, stomach upset, and diarrhea.

Continues on Back

Foamy Cutting Fluid

***** SECTION V – HEALTH HAZARD DATA *****

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush immediately with cool, clean water for 15 minutes, or until irritation subsides.

INGESTION: Aspiration Hazard – Do not induce vomiting. Seek immediate medical attention.

SKIN: Remove by wiping. Wash with mild soap and water.

INHALATION: Remove to fresh air. If breathing is stopped, start artificial respiration. Never give anything by mouth to an unconscious person. Wash clothing thoroughly before reuse. If irritation develops or persists, see a physician.

***** SECTION VI – REACTIVE DATA *****

CONDITIONS TO AVOID	: Storage Over 100 F
INCOMPATIBILITY	: Oxidizing & Reducing Agents
DECOMPOSITION PRODUCTS	: Oxides Of Carbon, Nitrogen, Hydrogen Chloride
HAZARDOUS POLYMERIZATION	: Will Not Occur

***** SECTION VII – SPILL AND LEAK PROCEDURES *****

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Absorb Spill On Inert Solid. Prevent Sewer, Drain, And Waterway Contamination.

WASTE DISPOSAL METHOD:

Dispose Of In Accordance With Federal, State, And Local Regulations.

***** SECTION VIII – SPECIAL PROTECTION INFORMATION *****

RESPIRATORY PROTECTION	: NIOSH Approved Organic Vapor Type At High Vapor Levels
VENTILATION	: As Needed To Keep Vapor Levels Below TLV (SEC. II)
PROTECTIVE GLOVES	: Rubber
EYE PROTECTION	: Goggles
OTHER PROTECTIVE EQUIPMENT	: Apron, Eye Wash

***** SECTION IX – SPECIAL PRECAUTIONS *****

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Store in a cool dry area. Avoid ignition sources. Keep container closed when not in use.

OTHER PRECAUTIONS:

After the container has been emptied, it may contain hazardous residues. Avoid sparks and open flame. Do not cut, puncture, or weld on or near the container. Do not reuse the container for any purpose until properly reconditioned.

The above mentioned information is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is expressed or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume responsibility for the results of its use. This information is furnished on the condition the person receiving it shall make his own determination as to the suitability of the material for his particular use and on the condition he assume the risk of his use thereof.

HMIS HAZARD CLASS:	Health	1 (Slight)
	Fire	2 (Moderate)
	Reactivity	0 (Least)
	Personal Protection	B