

Fiebing PRIME NEATSFOOT OIL COMPOUND, AEROSOL

IDENTITY (As Used on Label and List): Prime Neatsfoot Oil Compound, Aerosol

SECTION I

MANUFACTURER'S NAME: FIEBING COMPANY, INC.

516 SOUTH 2ND STREET
MILWAUKEE, WI 53204

EMERGENCY TELEPHONE NUMBER: (800) 424-9300

TELEPHONE NUMBER FOR INFORMATION: (414) 271-5011

DATE PREPARED: May, 1993

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components (Specific Chemical Identity: Common Name(s))	OSHA PEL	ACGIH TLV	% (optional)
Propane (CAS Reg No. 74-98-6) Other Limits Recommended: N.A.	1000 ppm	N.E.	-
Butane (CAS Reg No. 106-97-8) Other Limits Recommended: N.A.	N.E.	800 ppm	-
Severely Hydrotreated Heavy Naphthenic Distillate (CAS Reg No. 64742-52-5)			-
Severely Hydrotreated Light Naphthenic Distillate (CAS Reg No. 64742-53-6)			-
Exposure limit for total	5 mg/m3	5mg/m3	
Severely Hydrotreated		(TLV/TWA)	
Naphthenic Petroleum		10 mg/m3	
Distillate in air:		TLV/STEL)	
Other Limits Recommended: None			

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: -44 deg to over 300 deg F
 VAPOR PRESSURE (mm Hg.) In can @ 70 deg F: Approx. 45 psig
 VAPOR DENSITY (AIR = 1) Approx.: 4.9
 SPECIFIC GRAVITY (H2O = 1) Approx.: 0.80
 MELTING POINT: N.D.
 EVAPORATION RATE (Butyl Acetate = 1): 0.1
 SOLUBILITY IN WATER: Negligible
 APPEARANCE AND ODOR: Clear yellowish liquid, slight
 characteristic petroleum hydrocarbon odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method Used): Estimated - 156 deg F
 FLAMMABLE LIMITS:
 LEL: 1.9
 UEL: 9.5
 EXTINGUISHING MEDIA: Foam, dry chemical, carbon dioxide.
 SPECIAL FIRE FIGHTING PROCEDURES: Avoid possible
 accumulations of vapors at floor level, as vapor is
 heavier than air. Self-contained breathing apparatus and
 protective clothing should be worn in fighting fires
 involving chemicals.
 UNUSUAL FIRE AND EXPLOSION HAZARDS: Avoid possible bursting
 of aerosol cans. Do not store where temperatures may
 exceed 120 deg F. Do not puncture or incinerate.

SECTION V - REACTIVITY DATA

STABILITY: Stable
 CONDITIONS TO AVOID: Heat, sparks, flames, strong
 oxidizers.
 INCOMPATIBILITY (Materials to Avoid): Strong oxidizers.
 HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Carbon monoxide and
 various organic compounds may be released if burned.
 HAZARDOUS POLYMERIZATION: Will Not Occur
 CONDITIONS TO AVOID: None known.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES: Although
 reasonable care has been taken in the preparation of this
 document, we extend no warranties and make no
 representation as to the accuracy or completeness of the
 information contained therein, and assume no responsibility
 regarding the suitability of this information for the
 user's intended purposes or for the consequences of its
 use. Each individual should make a determination as to the
 suitability of the information for their particular
 purpose(s). A request has been made to the manufacturer to
 approve the contents of this material safety data sheet.

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY:

INHALATION? Yes

SKIN? Yes

INGESTION? Yes

HEALTH HAZARDS (Acute and Chronic): Inhalation - Dizziness,
 nausea, headache, may cause mild irritation of upper
 respiratory tract. Skin Contact - Irritation upon
 prolonged or repeated contact. Eye Contact - May cause
 irritation.

CARCINOGENICITY:

NTP? No

IARC MONOGRAPHS? No

OSHA REGULATED? No

SIGNS AND SYMPTOMS OF EXPOSURE: As noted above.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Preexisting skin and respiratory disorders may be
 aggravated by exposure to this product.

EMERGENCY AND FIRST AID PROCEDURES: Inhalation - Remove to
 fresh air. Artificial respiration. Get medical attention.
 Skin Contact - Wash with soap and water. Remove and wash
 contaminated clothing. Eye Contact - Flush with plenty of
 water for 15 minutes. Ingestion - Call a physician or
 poison control center immediately. Proper treatment is
 dependent on condition of patient and amount ingested.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Ventilate area well. Avoid any sources of ignition for
 flammable liquid or vapor. Soak up on suitable absorbent
 material.

WASTE DISPOSAL METHOD: Dispose of according to federal,
 state, county and local regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not
 store where temperatures may exceed 120 deg F. Do not
 store near heat, flame, fire or sparks.

OTHER PRECAUTIONS: Avoid excessive breathing of vapor or
 mist. Do not spray in direction of body. Avoid skin and
 eye contact. Do not ingest. Use as directed.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION (Specify Type): If TLV exceeds NIOSH
 approved self-contained breathing apparatus or
 respirator.

VENTILATION:

LOCAL EXHAUST: Adequate to maintain vapors or mists at
 5mg/m3

MECHANICAL (General): Sufficient

SPECIAL: None

OTHER: N.A.

PROTECTIVE GLOVES: Impervious solvent resistant.

EYE PROTECTION: Safety goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Apron, eye
 fountain.

WORK/HYGIENIC PRACTICES: Wash thoroughly after use.

N.D. = NOT DETERMINED

N.E. = NOT ESTABLISHED

N/A = NOT APPLICABLE

Upon receipt a new MSDS will be made available.

COMPAS Code: 12970540