

# MATERIAL SAFETY DATA SHEET

SDS Name: RED DUCT LINER ADHESIVE

MSDS Number: 15-146R

MSDS Last Updated: MAR-30-2005

Printed On: 03/30/05

Page Number: 1

## SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: RED DUCT LINER ADHESIVE  
CAS Number: MIXTURE  
Hazard Rating: Health: 1 Fire: 3 Reactivity: 0 PPI: G

Company Identification: ITW TACC  
AIR STATION INDUSTRIAL PARK  
ROCKLAND MA 02370

Telephone/Fax: (781) 878-7015 (781) 871-6727  
Chemtrec (24 Hour): (800) 424-9300

Trade Name: 15-146  
Product Code: 15-146  
DOT Hazard Class 3  
UN Number: 1133  
Shipping Name: ADHESIVES  
Packing Group: II

## SECTION II - HAZARDOUS INFORMATION

Ingredient Name	CAS Number	Percent	TSCA
LIGHT ALIPHATIC NAPHTHA	64742-89-8	25-50	Y
HEXANE	110-54-3	10-30	Y
CYCLOHEXANE	110-82-7	1-5	Y

## SECTION III - PHYSICAL DATA

Appearance/Color: RED  
Boiling Range: 156. F  
Evaporation Rate: Faster than n-Butyl Acetate  
% Volatile Weight: 69.86%  
% Volatile Volume: Not Available  
Specific Gravity: 0.75792

# MATERIAL SAFETY DATA SHEET

SDS Name: RED DUCT LINER ADHESIVE

SDS Number: 15-146R

MSDS Last Updated: MAR-30-2005

Printed On: 03/30/05

Page Number: 3

lungs due to vomiting can cause chemical pneumonitis which can be fatal.

INHALATION: Remove individual to fresh air and if breathing is difficult, administer oxygen.

## SECTION VI - REACTIVITY DATA

Stability: This product is stable

Hazardous Polymerization: Hazardous polymerization will not occur

### INCOMPATIBILITY:

Strong oxidizing agents, strong acids and bases.

### CONDITIONS TO AVOID:

Fire, sparks, static electricity.

### HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon monoxide, carbon dioxide.

## SECTION VII - SPILL OR LEAK PROCEDURES

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Keep spectators away. Eliminate all ignition sources (flames, hot surfaces and sources of electrical, static or frictional sparks). Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered metal containers for recovery or disposal, or remove with inert absorbent. Use only non-sparking tools. Place absorbent diking materials in covered metal containers for disposal. Prevent contamination of sewers, streams and groundwater with spilled material or used absorbent.

### WASTE DISPOSAL METHOD:

Dispose of in accordance with federal, state and local regulations.

## SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

### Occupational Exposure Limits:

	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
LIGHT ALIPHATIC NAPHTHA					
100.00 PPM	N/est	N/est	N/est	500.00 PPM	
HEXANE					
400.00 PPM	N/est	500.00 PPM	N/est	500.00 PPM	

MATERIAL SAFETY DATA SHEET

MSDS Name: RED DUCT LINER ADHESIVE  
SDS Number: 15-146R

MSDS Last Updated: MAR-30-2005  
Page Number: 5

Printed On: 03/30/05

-----  
CYCLOHEXANE 110-82-7 1-5

The following ingredients are registered for TSCA 12B  
Ingredient Name CAS Number

Percent

HEXANE 110-54-3 10-30

CYCLOHEXANE 110-82-7 1-5

=====

DISCLAIMER

=====

\*\*\*\*\* NOTICE \*\*\*\*\*

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of ITW TACC. The data on this sheet relates only to the specific material designated herein. ITW TACC assumes no legal responsibility for use or reliance upon these data.