



# MATERIAL SAFETY DATA SHEET

Pre-Mixed Floor Patch

## Section 1: PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Pre-Mixed Floor Patch  
**Product Use:** Patching Material  
**Manufacturer/Supplier:** Custom Building Products  
13001 Seal Beach Blvd  
Seal Beach, CA  
90740  
**Phone Number:** (562) 598-8808  
**Emergency Phone:** INFOTRAC 1-800-535-5053 (US and Canada)  
INTERNATIONAL + 1-352-323-3500  
**Date of Preparation:** November 23, 2011 **Revision Date:** September 11, 2012

## Section 2: HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

CAUTION

MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

**Potential Health Effects:** See Section 11 for more information.

**Likely Routes of Exposure:** Skin contact, skin absorption, eye contact, inhalation, and ingestion.

**Eye:** May cause eye irritation.

**Skin:** May cause skin irritation.

**Ingestion:** May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

**Inhalation:** May cause respiratory tract irritation.

**Chronic Effects:** Prolonged or repeated contact may dry skin and cause irritation.

**Signs and Symptoms:** Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

**Medical Conditions Aggravated By Exposure:** Asthma. Allergies.

**Target Organs:** Skin, eyes, gastrointestinal tract and respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**Potential Environmental Effects:** May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

## Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS #	Wt. %
1,4-Dioxane	123-91-1	<0.1
Ethylene oxide	75-21-8	<0.1
Acetaldehyde	75-07-0	<0.1
Calcium carbonate	1317-65-3	10 - 30
Silica, crystalline, quartz	14808-60-7	15 - 40
Ethylene glycol	107-21-1	0.5 - 1.5
Ethyl acrylate	140-88-5	<0.1
N-(Hydroxymethyl)acrylamide	924-42-5	<0.1



# MATERIAL SAFETY DATA SHEET

Pre-Mixed Floor Patch

## Section 4: FIRST AID MEASURES

- Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.
- Skin Contact:** In case of contact, immediately flush skin with plenty of water. Call a physician if irritation develops and persists.
- Inhalation:** If breathed in, move person into fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
- Ingestion:** DO NOT induce vomiting. If victim is conscious and alert, give 2 cupfuls of water. Never give anything by mouth to an unconscious person. Seek medical attention or call poison control.

**General Advice:** In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).

**Note to Physicians:** Symptoms may not appear immediately.

## Section 5: FIRE FIGHTING MEASURES

**Flammability:** Not flammable by OSHA/WHMIS criteria.

**Means of Extinction:**

**Suitable Extinguishing Media:** Powder, water spray, foam, carbon dioxide.

**Unsuitable Extinguishing Media:** Not available.

**Products of Combustion:** May include, and are not limited to: oxides of carbon.

**Explosion Data:**

**Sensitivity to Mechanical Impact:** Not available.

**Sensitivity to Static Discharge:** Not available.

**Protection of Firefighters:** Containers may explode when heated. Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

## Section 6: ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental Precautions:** Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

**Methods for Containment:** Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

**Methods for Clean-Up:** Scoop up material and place in a disposal container. Provide ventilation.

**Other Information:** Not available.

## Section 7: HANDLING AND STORAGE

**Handling:**

Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking.



# MATERIAL SAFETY DATA SHEET

Pre-Mixed Floor Patch

## Storage:

Keep out of the reach of children. Keep container tightly closed. Do not store at temperatures above 49 °C / 120 °F.

## Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Guidelines

Ingredient	Exposure Limits	
	OSHA-PEL	ACGIH-TLV
1,4-Dioxane	100 ppm	20 ppm
Ethylene oxide	1 ppm	1 ppm
Acetaldehyde	200 ppm	Not available.
Calcium carbonate	15 mg/m <sup>3</sup> (total); 5 mg/m <sup>3</sup> (resp) ((10 mg/m <sup>3</sup> )/(%SiO <sub>2</sub> +2) TWA (resp)); ((30 mg/m <sup>3</sup> )/(%SiO <sub>2</sub> +2) TWA (total)); ((250)/(%SiO <sub>2</sub> +5) mppcf TWA (resp))	10 mg/m <sup>3</sup>
Silica, crystalline, quartz		0.025 mg/m <sup>3</sup>
Ethylene glycol	Not available.	50 ppm
Ethyl acrylate	5 ppm	5 ppm
N-(Hydroxymethyl)acrylamide	Not available.	Not available.

**Engineering Controls:** Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

### Personal Protective Equipment:

**Eye/Face Protection:** Wear eye/face protection.

**Hand Protection:** Wear suitable gloves.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** In case of insufficient ventilation, wear suitable respiratory equipment.

**General Hygiene Considerations:** Handle according to established industrial hygiene and safety practices.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Paste-like compound.
<b>Color:</b>	Gray.
<b>Odor:</b>	Mild acrylic odor.
<b>Odor Threshold:</b>	Not available.
<b>Physical State:</b>	Paste.
<b>pH:</b>	9.0-10.0
<b>Viscosity:</b>	Not available.
<b>Freezing Point:</b>	~ 0 °C (~ 32 °F).
<b>Boiling Point:</b>	Not available.
<b>Flash Point:</b>	Not available.
<b>Evaporation Rate:</b>	Not available.
<b>Lower Flammability Limit:</b>	Not available.
<b>Upper Flammability Limit:</b>	Not available.
<b>Vapor Pressure:</b>	Not available.



# MATERIAL SAFETY DATA SHEET

Pre-Mixed Floor Patch

<b>Vapor Density:</b>	Not available.
<b>Relative Density:</b>	~ 1.6 g/mL.
<b>Solubility in Water:</b>	Partially Miscible.
<b>Coefficient of Water/Oil Distribution:</b>	Not available.
<b>Auto-ignition Temperature:</b>	Not available.
<b>Percent Volatile, wt. %:</b>	~ 20%
<b>VOC content:</b>	27 g/L (Calculated).

## Section 10: STABILITY AND REACTIVITY

**Stability:** Stable under normal storage conditions.

**Conditions of Reactivity:** Heat. Incompatible materials.

**Incompatible Materials:** Strong oxidizers.

**Hazardous Decomposition Products:** May include, and are not limited to: oxides of carbon.

**Possibility of Hazardous Reactions:** No dangerous reaction known under conditions of normal use.

## Section 11: TOXICOLOGY INFORMATION

### EFFECTS OF ACUTE EXPOSURE

#### Component Analysis

<b>Ingredient</b>	<b>LD<sub>50</sub> (oral)</b>	<b>LC<sub>50</sub></b>
1,4-Dioxane	4200 mg/kg, rat	48.5 mg/L 4hr, rat
Ethylene oxide	72 mg/kg, rat	Not available.
Acetaldehyde	1930 mg/kg, rat	Not available.
Calcium carbonate	6450 mg/kg, rat	Not available.
Silica, crystalline, quartz	500 mg/kg, rat	Not available.
Ethylene glycol	4000 mg/kg, rat	> 200 mg/m <sup>3</sup> 4hr, rat
Ethyl acrylate	800 mg/kg, rat	1414 ppm 4hr, rat
N-(Hydroxymethyl)acrylamide	400 mg/kg, rat	Not available.

**Eye:** May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

**Skin:** May cause skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

**Ingestion:** May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

**Inhalation:** May cause respiratory tract irritation.

### EFFECTS OF CHRONIC EXPOSURE

**Target Organs:** Not available.

**Chronic Effects:** Hazardous by WHMIS/OSHA criteria.

**Carcinogenicity:** Hazardous by WHMIS/OSHA criteria.



# MATERIAL SAFETY DATA SHEET

Pre-Mixed Floor Patch

## Ingredient

1,4-Dioxane  
Ethylene oxide  
Acetaldehyde  
Calcium carbonate  
Silica, crystalline, quartz  
Ethylene glycol  
Ethyl acrylate  
N-(Hydroxymethyl)acrylamide

## Chemical Listed as Carcinogen or Potential Carcinogen \*

G-A3, I-2B, N-2, CP65  
O, G-A2, I-1, N-1, CP65  
G-A3, I-1, I-2B, N-2, CP65  
Not listed.  
G-A2, I-1, N-1, CP65  
G-A4  
G-A4, I-2B, CP65  
I-3, CP65

\* See Section 15 for more information.

**Mutagenicity:** Not hazardous by WHMIS/OSHA criteria.

**Reproductive Effects:** Not hazardous by WHMIS/OSHA criteria.

## Developmental Effects:

**Teratogenicity:** Hazardous by WHMIS/OSHA criteria.

**Embryotoxicity:** Hazardous by WHMIS/OSHA criteria.

**Respiratory Sensitization:** Not hazardous by WHMIS/OSHA criteria.

**Skin Sensitization:** Not hazardous by WHMIS/OSHA criteria.

**Toxicologically Synergistic Materials:** Not available.

## Section 12: ECOLOGICAL INFORMATION

**Ecotoxicity:** May cause long-term adverse effects in the aquatic environment.

**Persistence / Degradability:** Not available.

**Bioaccumulation / Accumulation:** Not available.

**Mobility in Environment:** Not available.

## Section 13: DISPOSAL CONSIDERATIONS

### Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

## Section 14: TRANSPORTATION INFORMATION

### DOT Ground Classification

Not regulated

### TDG Ground Classification

Not regulated

### IATA Classification

Not regulated

### IMDG Classification

Not regulated



# MATERIAL SAFETY DATA SHEET

Pre-Mixed Floor Patch

## Section 15: REGULATORY INFORMATION

### Federal Regulations

**Canadian:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

**US:** MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200).

### SARA Title III

Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
1,4-Dioxane	Not listed.	Not listed.	100	313
Ethylene oxide	1,000	10	10	313
Acetaldehyde	Not listed.	Not listed.	1,000	313
Calcium carbonate	Not listed.	Not listed.	Not listed.	Not listed.
Silica, crystalline, quartz	Not listed.	Not listed.	Not listed.	Not listed.
Ethylene glycol	Not listed.	Not listed.	5,000	313
Ethyl acrylate	Not listed.	Not listed.	1,000	313
N-(Hydroxymethyl)acrylamide	Not listed.	Not listed.	Not listed.	313

### State Regulations

**New Jersey Right-To-Know:** Calcium carbonate, Silica Quartz, Ethylene glycol. **Pennsylvania**

**Right-To-Know:** Limestone, Quartz, 1,2-Ethanediol, Sodium hydroxide. **Massachusetts**

**Right-To-Know:** Calcium carbonate, Quartz, Ethylene glycol.

### California Proposition 65:

This product contains a chemical or chemicals known to the State of California to cause cancer.

### Global Inventories

Ingredient	Canada DSL/NDSL	USA TSCA
1,4-Dioxane	DSL	Yes.
Ethylene oxide	DSL	Yes.
Acetaldehyde	DSL	Yes.
Calcium carbonate	NDSL	Yes.
Silica, crystalline, quartz	DSL	Yes.
Ethylene glycol	DSL	Yes.
Ethyl acrylate	DSL	Yes.
N-(Hydroxymethyl)acrylamide	DSL	Yes.

All ingredients are on DSL/NDSL and TSCA inventories or are exempt from listing.

### HMIS - Hazardous Materials Identification System

Health - 1\*

Flammability - 0

Physical Hazard - 0

PPE - B

### NFPA - National Fire Protection Association:

Health - 1

Fire - 0

Reactivity - 0

**Hazard Rating:** 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme



# MATERIAL SAFETY DATA SHEET

Pre-Mixed Floor Patch

## WHMIS Classification(s):

Class D2A - Carcinogenicity  
Class D2A - Teratogenicity and Embryotoxicity  
Class D2A - Chronic Toxic Effects  
Class D2B - Skin/Eye Irritant

## WHMIS Hazard Symbols:



## SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

**OSHA (O)** Occupational Safety and Health Administration.

**ACGIH (G)** American Conference of Governmental Industrial Hygienists.  
A1 - Confirmed human carcinogen.  
A2 - Suspected human carcinogen.  
A3 - Animal carcinogen.  
A4 - Not classifiable as a human carcinogen.  
A5 - Not suspected as a human carcinogen.

**IARC (I)** International Agency for Research on Cancer.  
1 - The agent (mixture) is carcinogenic to humans.  
2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.  
2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.  
3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.  
4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

**NTP (N)** National Toxicology Program.  
1 - Known to be carcinogens.  
2 - Reasonably anticipated to be carcinogens.

## Section 16: OTHER INFORMATION

### Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

**Expiry Date:** September 11, 2015

**Version #:** 1.1

**Prepared by:** Nexreg Compliance Inc.  
Phone: (519) 488-5126  
[www.nexreg.com](http://www.nexreg.com)